



AMERITEK 2000 TABBER FROM SECAP

TAB & WAFER SEAL AFFIXER

- Heavy Duty Tabletop Unit
- High Speed, Versatile Operation
- Operates In-Line or Off-Line
- Single, Double, or Triple Tab



PRINTERS



TABBERS



FOLDERS AND
INSERTERS



SOFTWARE

TECHNICAL SPECIFICATIONS

SPEED

Production Rate:

Single Tab: Up to 20,000 pieces/hr.
 Double Tab: Up to 15,000 pieces/hr.
 Triple Tab: Up to 12,000 pieces/hr.
(based on 8.5" length product)

Transport Belt:

0 to 375 ft./min

Tabbing Head:

0 to 375 ft./min.

MEDIA

Size:

Minimum: 3" x 5"
 Maximum: 12" x 14"

Thickness:

Minimum: 20# single sheet
 Maximum: 3/8"

Stock: Coated, bond, recycled, card

TABS/LABELS

Types:

Tabs (single, double, triple), wafer seals, labels, stamps, customized stickers, scratch-offs, machine grade paper and adhesive, clear, translucent, unperfed, vertical perfed.

Note: Clear and translucent tabs require an "engineered backer" with registration marks for indexing.

Roll Size:

Up to 13.5" diameter mounted on a 3" core, approximately 20,000 1" tabs or 12,500 1.5" tabs.

Backer:

Approx. 1/16" - 1/4" larger than tab/label, typical gap between tabs/labels is 1/8" to 1/16".

Width:

Minimum: 3/4"; Maximum: 1-3/4"

TAB PLACEMENT

Accuracy: +/- 1/8" repeatability.

PHYSICAL CHARACTERISTICS:

Dimensions: 28"W x 34.5"D x 38"H
 Weight: 160 lbs.
 Power: 115V, 5 amp

CERTIFICATION

TUV pending, FCC pending

Complies with USPS specifications for tab placement and application.

Specifications subject to change without notice. Speeds may vary depending on material and application.



Ameritek 2000 Tabber shown with FR 170 feeder and conveyor.

DETAILS

Ameritek 2000 Tabber from Secap shown in-line with the SA5300 PRO.

The Ameritek 2000 Tabber offers heavy duty construction and high productivity from a table-top unit that handles a variety of media while maintaining precise tab placement.

1. In-line Productivity

Tabber shown operating in-line with the Secap® 5300 PRO inkjet system. Feed, print, tab and stack (conveyor not shown).

2. Simple Controls and Easy to Use

Set up and operation is easy with the electronic control panel allowing precise adjustments for material handling and control to optimize output.

3. Superior Material Handling

Precision registration transport guides offer superior material

handling in a variety of size and thickness. Streamlined tab threading allows for easy job changeovers.

4. Applies a Variety of Adhesive Material

Reel holds up to 20,000 tabs. Use tabber to apply:

- Up to 3 tabs or wafer seals in one pass for postal automation discounts.
- Labels and stamps, along with customized stickers and scratch-offs to personalize and create action promotions.

5. Meets High Performance Standards

Sturdy, tabletop unit is designed to meet your most demanding tabbing applications providing consistent operation for rugged mailing environments.

PERFECT FOR:

Lettershops, Commercial Printers, Quick Printers, Pro Mailers, Print Shops, Fulfillment Houses, as well as anyone else needing to seal open-ended media at production speeds.

Ask about Secap's complete line of mailstream solutions:



PRINTERS



TABBERS




FOLDERS AND INSERTERS



SOFTWARE

Available from your authorized and certified Secap dealer.



Contact the dealer above or call 800.523.0320 for a Secap dealer near you.



10 Clipper Road
 West Conshohocken, PA
 19428-2721
 800.523.0320
 610.825.6205
 610.825.1397 (fax)
 www.secap.com